
FORD TRUCKS 1842T EURO6





Tractor			
4x2			
Euro 6			
Extra High Roof Sleeper Cab			
3600			
Ecotorq 12,7 liters			
12740			
130 mm x 160 mm			
420 PS (308,9 kW) / 1800 rpm			
2150 Nm / 1000-1300 rpm			
17 +/- 0,5 : 1			
50 L			
37 L (57 L with Intarder)			
430 mm Single Disc			
ZF 16S 2230 (13,805 - 0,836)			
ZF 12 TX 2210 (16,688-1)			
Power Assisted Single Circuit			
10 mm			
500 MPa			
90 mm Parabolic Leaf Springs / Air Suspension			
Single Reduction			

Chassis Thickness	10 mm
Chassis Strength	500 MPa
Suspension (Front / Rear)	90 mm Parabolic Leaf Springs / Air Suspension
Axle	Single Reduction
Axle Ratio - 1200 mm 5 th Wheel (Manual / Automated)	3,08 / 2,64
Axle Ratio - 1100 mm 5 th Wheel (Manual / Automated)	2,85 / 2,47
Tyres - 1200 mm 5 th Wheel (Manual / Automated)	295/80 R 22,5
Tyres - 1100 mm 5 th Wheel (Manual / Automated)	315/70 R 22,5
Wheel Rim	Steel Wheel (22,5 x 9)
Braking System	
Brakes (Ø mm x mm Length)	430 x 45 - Disc Brakes

Brakes (Ø mm x mm Length)

Braking System

Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater
Engine Brake Power

max. 340 kW (Engine Level)
Intarder Power

max. 600 kW / continuous 160 kW

Electrical System

78 L

Battery 24V, 2 x 12V 180 Ah
Alternator / Starter Motor 130 A / 6,5 kW

Tanks
Fuel Tank 600 L Aluminium

SCR Tank



Dimensions (mm)			
5 th Wheel Height		1200	
Front Overhang		1500	
Wheelbase		3600	
Overall Length		6150	
Overall Cab Length		2305	
Total Height		3950 (Extra High Roof); 3104 (Low Roof)	
Overall Vehicle Width (Excluding Mirrors)		2540	
Chassis Width		866	
Rear Overhang		1050	
Chassis Height-Front		225	
Chassis Height-Rear		285	
Ground Clearance-Front		320	
Ground Clearance-Rear		360	
Turning Radius		7500	
Weights (kg)	1. Axle	2. Axle	Total
Technically Permissible Weights	7100	12600	19000
Kerb Weight	5155	2194	7269
Payload	1945	10406	11731
GVM (Legal)	7100	11500	18000

STANDARD EQUIPMENT

- Air Conditioner
- Radio/CD Player
- Extra High Roof Cab with Double Bed
- Dry Type Cab Heater
- Cab Air Suspension
- Cruise Control
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Electrically Operated Sunroof
- Front and Rear Vehicle Antiroll Bars
- Disc Brakes
- Electronic Brake System (EBS) and Anti-Lock Brake System (ABS)
- Active Emergency Brake System (AEBS)
- Electronic Brake Force Control
- Brake Assistant
- Electronic Stability Control (ESP)
- Pad Wear Indicator
- Lane Departure Warning System (LDWS)
- Auto Light Sensor
- Rain Sensor
- Immobilizer
- Single Key with Remote Control and Central Locking
- Home Safe and Approach Lights
- Differential Lock
- Digital Tachograph
- Switchable Air Compressor for Improved Fuel Economy
- Variable Steering Pump for Improved Fuel Economy
- Hill Launch Assist
- Coupling Force Control
- Front Fog Lamps
- Axle Load Indicator

OPTIONAL EQUIPMENT

- Automated Transmission (With Different Usage Modes)
- Intarder
- ADR Package
- Low Roof Sleeper Cab with Single Bed
- Wet Type Cab Heater
- Cold Pack with Wet Type Cab Heater
- Cold Pack with Dry & Wet Type Cab Heater
- Electrically Operated Cab Tilting
- Engine Driven PTO
- Transmission Driven PTO
- 5th Wheel Options *: 1050, 1100, 1150, 1200, 1250, 1300 mm
- Spare tyre and carrier
- Jost 5th Wheel
- Dual Fuel Tank (450L)
- Side Skirt
- Spoiler**
- Electrically Operated Cab Tilting
- Upper Bed

^{* 1050} mm 5th wheel height is available with 315/60 R22,5 tyres

^{* 1100} mm 5th wheel height is available with 315/70 R22,5 tyres

^{* 1150} mm 5th wheel height is available with 295/80 R22,5 tyres

^{* 1200} mm 5th wheel height is available with 295/80 R22,5 or 315/80 R22,5 tyres

^{* 1250} mm 5th wheel height is available with 295/80 R22,5 tyres * 1300 mm 5th wheel height is available with 315/80 R22,5 tyres

³⁰⁰ mm 5th wheel height is available with 315/80 R22,5 ** Not Available with Low Roof Sleeper Cab Version