۲

FORD TRUCKS 1848T EURO6





Basic Features			
Vehicle Type	Tractor		
Axle	4x2		
Emission	Euro 6		
Cabin Type	Extra High Roof Sleeper Cab		
Wheelbase (mm)	3600		
Engine			
Туре	Ecotorq 12,7 lt		
Displacement (cc)	12740		
Diameter x Stroke	130 mm x 160 mm		
Power	480 PS (353 kW) / 1800 rpm		
Torque	2500 Nm / 1000 - 1200 rpm		
Compression Ratio	17 +/- 0,5 : 1		
Oil Filling Volume	50 L		
Coolant Volume	37 L (57 L with Intarder)		
Transmission			
Clutch	430mm Single Disc		
Automated Transmission	ZF 12 TX 2620 TRAXON (16,688 - 1)		
Steering			
	Power Assisted Single Circuit		
Chassis			
Chassis Thickness (mm)	8mm with Local Reinforcement		
Chassis Strength	500MPa		
Suspension (Front/Rear)	90 mm Parabolic Leaf Springs / Air Suspension		
Axle	Single Reduction		
Axle Ratio - 1200 mm 5 th Wheel	2,64		
Axle Ratio - 1100 mm 5 th Wheel	2,47		
Tyres - 1200 mm 5 th Wheel	295/80 R22.5		
Tyres - 1100 mm 5 th Wheel	315/70 R22.5		
Wheel Rim	22,5 x 9 Steel		
Braking System			
Brakes (Front/Rear) (Ø.mm x mm. Length)	430 x 45 Disc Brakes		
Braking System	Dual Brake Circuit – Air Processing Unit with Integrated Oil Seperator and Heater		
Engine Brake Power	max. 340 kW (Engine Level)		
Intarder Power	max. 600 kW / Continuous 160 kW		
Electrical System			
Battery	24V, 2 x 12V 180 Ah		
Alternator / Starter Motor	130 A / 6,5 kW		
Tanks			
Fuel Tank	600 L Aluminium		
SCR Tank	78 L		



۲

۲

۲

۲

Dimensions (mm)				
5 th Wheel Height		1100		
Front Overhang		1500		
Wheelbase		3600		
Overall Length		6150		
Overall Cab Length		2305		
Total Height	3945 (Extra High Roof) , 3104 (Low Roof)			
Overall Vehicle Width (Excluding Mirrors)		2540		
Chassis Width		866		
Rear Overhang		1050		
Chassis Height-Front		225		
Chassis Height-Rear		285		
Ground Clearance-Front		300		
Ground Clearance-Rear		255		
Turning Radius		7500		
Weights (kg)	1. Axle	2. Axle	Total	
Technically Permissible Weights	7100	12600	18000	
Kerb Weight	5113	1979	7092	
Payload	1987	10621	10908	
GVM (Legal)	7100	11500	18000	

STANDARD EQUIPMENT

• Air Conditioner

- Radio/CD Player
- Extra High Roof Cab with Double Bed
- Dry Type Cab Heater
- Air Suspended Cab
- Cruise Control
- Engine Brake
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Levelling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Electrically Operated Sunroof
- Front and Rear Vehicle Antiroll Bar
- Automated Transmission (with different usage modes)
- Disc Brakes

۲

- Electronic Brake System (EBS) and
- Anti-Lock Brake System (ABS)
- Active Emergency Brake System (AEBS)
 Electronic Brake Force Control
- Brake Assistant
- Electronic Stability Program (ESP)
- Brake Lining Wear Sensor
- Lane Departure Warning System
- Auto Light Sensor
- Rain Sensor
- Immobilizer
- Single Key with Remote Control and Central Locking
- Home Safe Light
- Approach Light
- Differential Lock
- Digital Tachograph
- Switchable Air Compressor for Improved Fuel Economy
- Variable Steering Pump for Improved Fuel Economy
- Hill Launch Assist
- Coupling Force Control
- Front Fog Lamps
- Axle Load Indicator

OPTIONAL EQUIPMENT

- Intarder
- ADR Pack
- Low Roof Sleeper Cab with Single Bed
- Cold Pack with Wet Type Cab Heater
- Cold Pack with Dry & Wet Type Cab Heater
- Engine Driven PTO
- Transmission Driven PTO & Interior Control Unit
- 5th Wheel Options * : 960, 1050, 1100, 1150,
- 1200, 1250, 1300 mm • Spare tyre and carrier
- Jost 5th Wheel
- Dual Fuel Tank (450L)
- Side Skirt
- Spoiler**
- 225 Ah Battery
- Electrically Operated Cab Tilting
- Upper Bed

* 960 mm 5th wheel height is available with Front Tire : 315/60 R 22,5 / Rear Tire: 295/60 R 22,5
* 1050 mm 5th wheel height is available with 315/60 R 22,5 tyres
* 1100 mm 5th wheel height is available with 315/70 R 22,5 tyres
* 1100 mm 5th wheel height is available with 295/80 R 22,5 tyres
* 1200 mm 5th wheel height is available with 295/80 R 22,5 tyres
* 1200 mm 5th wheel height is available with 295/80 R 22,5 tyres
* 1200 mm 5th wheel height is available with 295/80 R 22,5 tyres
* 1200 mm 5th wheel height is available with 295/80 R 22,5 tyres
* 1300 mm 5th wheel height is available with 315/80 R 22,5 tyres
* 1300 mm 5th wheel height is available with 315/80 R 22,5 tyres
* 1300 mm 5th wheel height is available with 315/80 R 22,5 tyres

This leaflet includes products designed for Ford Trucks vehicles. It provides information about the current technical specifications and the standard or optional accessories available as of the date it was issued. Features of standard and optional accessories of the vehicles may be changed from time to time. For this reason, please consult our Authorized Dealers to obtain updated and accurate information on the features of the vehicle you wish to buy. For the aforementioned reason, this leaflet does not constitute an assurance as to the specifications listed herein. The images used in this leaflet may be different from the vehicles on sale. The technical specifications provided herein are for standard vehicles. Selection of any optional accessories might cause differences from these specifications. ۲